

## TECHNICAL DATA SHEET

PRODUCT	
POTASH FELDSPAR	Pure Potash Feldspar is used as a high temperature flux in both clay bodies and glaze preparation.

TYPICAL PROPERTIES (MEAN VALUES. THESE DO NOT REPRESENT A SPECIFICATION.)	
Appearance	Off White Odourless Powder
Particle Size	<5.0% on a 75 Micron Mesh
Specific Gravity	2.70 g/cm <sup>3</sup>
Moisture Content	1.0% maximum (when packed)
Storage	Store in dry conditions at 5-30°C

CHEMICAL ANALYSIS (MEAN VALUES. THESE DO NOT REPRESENT A SPECIFICATION.)		
Silicon Oxide	SiO <sub>2</sub>	69.5%
Aluminium Oxide	Al <sub>2</sub> O <sub>3</sub>	16.6%
Calcium Oxide	CaO	0.39%
Potassium Oxide	K <sub>2</sub> O	10.4%
Sodium Oxide	Na <sub>2</sub> O	2.3%
Iron Oxide	Fe <sub>2</sub> O <sub>3</sub>	0.12%
Titanium Oxide	TiO <sub>2</sub>	0.03%

PRODUCT SIZE
The products are available in 25kg Paper Bags, big bags and bulk.