

TECHNICAL DATA SHEET

| PRODUCT | | |
|-------------------------|---|--|
| SODIUM SILICATE 140S | Primarily used for the production of casting slips. | |

| TYPICAL ANALYSIS AND PROPERTIES (MEAN VALUES. THESE DO NOT REPRESENT A SPECIFICATION.) | | |
|--|-------------------|--|
| Cas No | 1344-08-8 | |
| Appearance | Colourless Liquid | |
| Total Solids | 52.5 – 54.5% | |
| Mol Ratio | 1.96 – 2.16 | |
| Weight Ratio | 1.86 – 2.06 | |
| pH (1%) | ±12 | |
| Insoluble | <0.05% | |
| Fe | <100ppm | |
| Density 1.686 ± 0.015 g/cm ³ | | |

| CHEMICAL ANALYSIS | | | | |
|--|------|--------------|--|--|
| (MEAN VALUES. THESE DO NOT REPRESENT A SPECIFICATION.) | | | | |
| Sodium Oxide | Na₂O | 17.3 – 18.3% | | |
| Silicon Oxide | SiO₂ | 34.7 – 36.7% | | |

| PRODUCT SIZE | |
|---|--|
| The products are available in Plastic Buckets (500ml, 1 litre, 5 litres). | |