Technical Data Sheet

Terracotta Fine 120's





Throwing

Casting

Firing Range: 1080-1180°C

Colour: Red

CAPACITÉ CAPACITÉ

Texture: Very Smooth



Bag Size: 12.5kg

1220°C 1200°C 1180°C 1160°C 1140°C 1120°C 1100°C 1080°C 1060°C	Fired at	
1180°C 1160°C 1140°C 1120°C 1100°C 1080°C	1220°C	
1160°C 1140°C 1120°C 1100°C 1080°C	1200°C	
1140°C 1120°C 1100°C 1080°C	1180°C	27
1120°C 1100°C 1080°C	1160°C	
1100°C 1080°C	1140°C	
1080°C	1120°C	
	1100°C	
1060°C	1080°C	
	1060°C	

Chemical Analysis %		
Chemical	Percentage	
SiO ₂	58.29	
TiO ₂	1.23	
AL ₂ O ₃	22.63	
Fe ₂ O ₃	6.89	
P ₂ O ₅	0.07	
CaO	0.44	
MgO	0.85	
K₂O	1.48	
Na₂O	0.07	

% Total Contraction		
1100°C	13%	
1200°C	х	

Thermal Expansion		
500°C	0.332	
600°C	0.469	

This technical information is only a guide, established from the characterisation and analysis of representative samples, and from routine production averages.

Product characteristics are subject to modifications.



